

Seek
thermal

FirePRO 300

PERSONAL THERMAL CAMERA FOR
IMPROVED SITUATIONAL AWARENESS
AND FIREFIGHTER SAFETY

KEY CAMERA SPECS

 Resolution	320 x 240
 Field of View	57° x 42°
 Durability	IP67 waterproof, 2 meter drop
 Detection	-20°C to 550°C (-4°F to 1022°F)
 Imaging	Mixed Gain with SV1
 Flashlight	300 Lumen LED

DOOLEY
TACKABERRY

dooleyackaberry.com



PN: FQ-AAAX

FirePRO 300 - the best innovation in personal thermal imaging. With FirePRO 300, you can equip every firefighter with an affordable and lightweight thermal camera to enhance situational awareness and improve firefighter safety.

Featuring our high resolution 320 x 240 sensor, FirePRO 300 provides firefighters with the ability to regain orientation in low visibility or blackout conditions. Additionally, Seek's game-changing Mixed Gain technology allows firefighters to see detail in the hottest and coolest regions of the scene at the same time without freezing and switching modes. Investing in a personal thermal imaging camera is an investment in your personal safety.

Designed and manufactured in the USA with global components. Thermal sensor designed and manufactured by Seek Thermal in Santa Barbara, CA USA.



KEY FEATURES

Made to endure and designed to be lightweight

Weighs just 325 grams and is IP67 waterproof with 2 meter drop durability

Mixed Gain with SV1 Image Optimization

See the hottest and coolest regions of the scene simultaneously without freezing or switching gain modes; details enhanced with SV1

Fast Frame Rate, High-Resolution Sensor

320 x 240 sensor size with 76,800 individual temperature pixels refresh 25 times a second

Up to 6 hours of use on a single charge

Long lasting rechargeable battery ensures FirePRO 300 is always ready

Ergonomic 90° viewing angle

90° viewing angle makes pointing the camera as easy as a cell phone

BENEFITS

Improve situational awareness

Visualize hazards invisible to the naked eye and navigate safely

Find your way out in zero visibility conditions

FirePRO 300 is your lifeline to regain orientation and reduce maydays

Execute the mission faster

Quickly locate victims and hot spots when every second counts

Reduce the potential for rekindles

Multiple firefighters can use Survey Mode during overhaul

Redundancy

Serves as a redundant backup to the team's decision making TIC


DOOLEY
TACKABERRY

TECHNICAL SUMMARY

SPECIFICATIONS	FIREPRO 300
Thermal Sensor	320 x 240
Field of View	57° x 42°
Germanium Window	Yes
Video Recording	Yes
Image Capture	Yes
Temperature Range	-4° to 1,022°F (-20° to 550°C)
Operating Temp (no limit)	-4° to 185°F (-20° to 85°C)
Operating Temp (5 min)	302°F (150°C)
Operating Temp (1 min)	500°F (260°C)
Frame Rate	> 25 Hz FastFrame
IP Rating	IP67 Waterproof
Impact Resistance	2 meter drop
Flashlight	300 Lumen LED
Display	2.8" TFT 320 x 240 screen resolution
Thermal Sensitivity	< 35 mK with SVI
Viewing Angle	Ergonomic 90° viewing angle
Imaging Modes	FIRE (with TI Basic & TI Basic +) and SURVEY
Size: H x W x D	5.3 x 3 x 1.8 inches (135 x 76 x 46 mm)
Weight	0.7 lbs (325 grams)
Battery Life	6 hours in thermal only 3.5 hours with flashlight on

IMAGING MODES

All modes use Mixed Gain with SVI Image Optimization



FIRE MODE
Using TI BASIC
(Without Spot Temp)



FIRE MODE
Using TI BASIC+
(With Spot Temp)



SURVEY MODE
With Spot Temp



SAMPLE IMAGES



Seek more at doileytackaberry.com

1515 W. 13th Street, Deer Park, TX 77536

Seek Thermal engineers, designs and manufacturers high quality thermal imaging products and core platforms for consumer, commercial, and heat sensing IoT data applications. With headquarters in Santa Barbara, California, the global hub of thermal imaging innovation, the company has developed breakthrough thermal imaging camera cores that will enable a range of affordable products for use at home, work and play. For more information visit thermal.com and follow #seekthermal on Instagram and @seekthermal on Twitter.